

ATS-309



ATS-309 tabber / Stamp Affixer



In-Line or Stand-Alone
Dual Head Multiple Tabber/Stamp Affixer

- Simultaneous 2-side tabbing; Simultaneous front and side tabbing
- Easy setup and smooth operation
- Fast! Speeds up to 25,000 pieces/hour placing accurate and tightly closed tabs
- Solid construction. Built to last!
- Capable of handling medium to high production consistently and reliably
- Optional synchronized detachable feeder for stand-alone applications

Specifications

One pass tab	1 to 3 per side or 1-3 on 1 side and 1 front
Standard tab	Minimum: 3/4" Maximum: 1-1/2"
Stamps	1 to 3
Media size (W X L)	Minimum: 5" x 3.5" Maximum: 11" x 15" (Detachable Feeder (12" X 17"))
Max mediathickness	1/4"
Tab size calibration	Manual or automatic
Tab placement setting	Manual or automatic
Tab sensor calibration	Manual or automatic
Media height adjustment	Tabbing Heads move up and down
Take-up spools	Two included
Production rate	Two sides tabbed simultaneously (1 tab - 25,000/h) Two sides tabbed simultaneously (2 tabs - 15,000/h) Two sides tabbed simultaneously (3 tabs - 10,000/h)
Production rates calculated with	Tri-fold 8-1/2" X 11"
Reel capacity	Two reels, 12" diameter each
Dimensions	28" W x 26" H (with reels) x 34" L (with feeder)
Weight	97 lbs.
Electrical	115VAC, 50/60Hz 240VAC 50/60 Hz available

Specifications are subject to change without notice.

TA & CO

Industrial Park Asper
Legen Heirweg 59
9890 Gavere

Tel. +32 9 281 08 50
Fax +32 9 281 08 70

