

ATS-12 tabber



The Most Efficient and Economical Tabber Ever!

- Automatically applies adhesive tabs or wafer seals to open-ended mail.
- Easy to set-up and operate.
- Seals a variety of media at speeds up to 12,000 pieces per hour.
- This modular tabbing system operates in-line or stands alone with its own feeder.
- Can be used in tandem for two-up tabbing.

Specifications

Dimensions	21-3/4" W x 19-1/2" H x 8-1/2" L
Speed	12,000 pieces per hour (8-1/2" x 11" tri-fold)
Media size	Minimum – 3" W x 5" L Maximum – 17" W x 18" L
Media thickness	Up to 3/16"
Tab size	Length – 5/8" to 1-1/2" (standard tabs)
Reel capacity	5,000 tabs
Label sensitivity control	Adjusts for density in tab/wafer seals
Feeder	Top load, bottom feed for continuous operation
Counter	Resettable 5-digit LCD
Power	110V/60Hz (2 AMP) (220V/50Hz available)
Shipping weight	44 lbs.
Options	Conveyor / Stacker



Specifications are subject to change without notice.

ATS-12 tabber

TA & CO
Industrial Park Asper
Legen Heirweg 59
9890 Gavere
Tel. +32 9 281 08 50
Fax +32 9 281 08 70

